

## Technical Specification Lift type Aritco Pluto

Pluto is a vertical platform lift for wheelchair users, specially designed to easily fit into your home. It is supplied complete with structure and cladding in either steel or glass panels and becomes an attractive feature in any home. Its simple design and ease of operation with large push buttons will provide an ideal solution for disabled access in all types of homes.

### Technical information

**Lift Type:** Platform lift type Pluto

**Lifting capacity:** 2 persons / 1 person in a wheelchair / 225 kg

**Lifting height:** max. 9000 mm

**Top height:** 2300 mm (fixed)

**Number of stops:** max. 4 stops

**Number of doors:** max. 1 door per floor

**Operator controls:** "Hold to run" buttons

**Drive system:** Screw / Nut

**Standard platform size:** 805 mm wide x 1080 mm deep

**Required floor area:** 880 mm wide x 1340 mm deep  
(for through Floor applications 910 mm wide x 1370 mm deep)

**Electrical connection:** 1 phase 230V 50Hz / 4.8A / 10A slow

**Speed:** 0.15 m/s

**Control supply:** 24 V

**Motor:** 1.5 kW

**Technical compliance:** European machine directive 98/37/EC

**Pit depth – if required:** 50 mm (also possible ramp)

**Standard colour:** White


**Standard specifications:** Indoor execution, self-closing mechanically interlocked entrance doors, battery operated emergency lowering, ceiling, full glass doors (GL).

**Main options:** Other RAL colours, School locking, automatic door openers, Safety glass panels for the shaft walls, Stainless steel door handle.

**Warranty:** 24 months, when serviced by an authorised agent



## Overview drawing



Measurements					
Platform length	1080 mm	Shaft depth	1340 mm	Top Height (fixed)	2300 mm
Platform width	805 mm	Shaft width	880 mm	Aperture depth	13700 mm
Door height	2000 mm	Shaft height**	5290 mm	Aperture width	910 mm
Door width	800 mm	Travel height	3000-9000 mm	(**) Depending on travel height and top height.	

## Options

### Doors

Door opener external  
Door opener internal  
Door opener mounted on frame  
Hold open arm for door closer  
Door faceplate Telemecanique  
Door faceplate ASSA (only for Sweden and Norway)

### Shaft

Support frame  
Cladded machine side  
Partly cladded machine side  
Ramp  
Glass panel

### Platform

Telephone socket/jacket  
Telephone  
Autodialer Safeline  
Faceplate with Telemecanique  
Faceplate with ASSA (only for Sweden and Norway)  
Floor cover Norament, rubber  
Floor cover SafeGuard, other finish  
Floor designation, specified  
Joystick  
Handrail, oak and brass

### Mast

School locking relay

### Electrical

Radio control 2 stop  
Radio control 3 stop  
Radio control 4 stop  
IR-control 2 stop  
IR-control 3 stop  
IR-control 4 stop  
Alarm Sounder

### Stainless steel

Door handle  
Handrail

